

48"/54"/60"

FasTrak

Commercial mowing comes home.

FEATURES

- Kawasaki FR Premium Engines - 3yr warranty
- 48" 54" or 60" side-discharge decks
- Toughest frame, front forks and deck in the industry
- Commercial grade welded steel decks
- Commercial duty ZT 3100 transmissions
- Commercial duty, serviceable deck spindles
- Comfortable foot-operated deck-lift system - 1.5" to 4.5"
- SmoothTrak™ steering with patented automatic park brake system
- 20" drive tires, 13" front caster tires
- 6.8 gallon fuel capacity
- Seat springs and slide with arm rests come standard
- SmoothTrak™ steering with patented automatic park brake system
- Standard, foldable Certified ROPS and seatbelt



* Original Purchaser Only

LIMITED
WARRANTY
4 YEAR | **400**
YEAR | HOUR

RESIDENTIAL

* See your local Hustler dealer for complete warranty details

LIMITED
WARRANTY
1 YEAR | **400**
YEAR | HOUR

COMMERCIAL

www.hustlerturf.com

HUSTLER 
Cutting Grass Not Corners

FastTrak

48" / 54" / 60"

Engines

Kawasaki
FR651V
21.5hp

Kawasaki
FR691V
23hp

Kawasaki
FR730V
24hp

More Engine Information:

• www.kawpower.com

ENGINE

Starter: 12-volt, (see engine manufacturer specs)

Ignition: Electronic

Charging System: 12-volt, (see engine manufacturer specs for current rating)

Fuel: Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

Fuel Filter: Replaceable, automotive-type

Cooling: Air cooled. Fly-wheel fan

Governor: Mechanical

TRACTION DRIVE SYSTEM

Type: Dual hydrostatic. Commercial-duty Hydro-Gear ZT 3100.

Hydrostatic Drive: V-belt drive from engine crankshaft

Ground Speed:

Forward: Infinitely variable: 0-8 mph (0-12.9 kph)

Reverse: 0-5 mph (0-8 kph) reverse

Steering: SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls.

Turning Radius: True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels.

Brakes:

Service: Hydrostatic dynamic braking.

Parking: Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged.

Tires:

Front: 13 x 6.5 – 6, smooth tread

Drive: 48 in: 20 x 10 – 10, turf tread
54 in: 20 x 12 – 10, turf tread
60 in: 20 x 12 – 10, turf tread

Capacities: Fuel System: 6.8 US gal (25.7 l)

GENERAL INFORMATION

Safety Features: Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor.

Seat: Molded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

Construction: Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel.

Controls: Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes.

Indicators: Engine warning light, Mechanical hour meter

Cup Holder: Single Cup Holder

DIMENSIONS

Height: 41.8 in (106.17 cm)

W/48 in Deck:

Length: 74.42 in (189.02 cm)

Overall width: 50.3 in (127.7 cm) w/discharge chute up

Tire-to-tire width: 47 in (119.38 cm)

Weight: 835 lbs (378 kg)

W/54 in Deck:

Length: 74.42 in (189.02 cm)

Overall width: 56.2 in (142.7 cm) w/discharge chute up

Tire-to-tire width: 51 in (129.54 cm)

Weight: 860 lbs (390 kg)

W/60 in Deck:

Length: 75.92 in (193 cm)

Overall width: 62.7 in (159.3 cm) w/discharge chute up

Tire-to-tire width: 51 in (129.54 cm)

Weight: 885 lbs (401 kg)

DECKS

Side-Discharge: 48" 54" or 60"

Type: Free-floating deck using three blades with center blade to the front. Deck is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain.

Construction: 11 ga, .120 in (.30cm) welded steel with 11 ga, .120 in (.30cm) doubler welded onto spindle mount areas. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge.

Cutting Heights: Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm).

Mowing Blades: Heavy-duty, heat-treated, low-lift steel blades.

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

Blade Tip Speed: (at 3600 RPM engine speed)

48 in: 18,600 fpm

54 in: 18,910 fpm

60 in: 18,410 fpm

Deck Drive: Single V-belt drive from engine with electric clutch to two spindles. Spring tension idler for extended belt life.

Spindles: Aluminum casting with steel shafts and sealed ball bearings.

Discharge Chute: High density, rubberized.

Width of Cut:

48 in: 47.1 in (119.63 cm)

54 in: 53.1 in (134.87 cm)

60 in: 59.1 in (150 cm)

Trim Capacity: (left side)

48 in: 2.0 in (5.08 cm)

54 in: 4.5 in (11.43 cm)

60 in: 5.9 in (15 cm)

ACCESSORIES

2-Bag Catcher: Commercial-duty, 7.2 bushel, rear-mounted, two-bag catcher with commercial belt-driven blower.

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Flex Forks™: Shock-absorbing front caster forks for a smooth ride and smoother cut

Other Accessories: Light Kit, Stripe Kit, Steering Extension Kit

Specifications subject to change without notice.

