

48"/54"/60"



Professional performance day in and day out.

FEATURES

- 48, 54, 60 Side Discharge deep decks with VX4® Technology
- PROVEN separate pumps and motors
- 11 mph
- 10.3 gallon fuel capacity
- 54, 60 Rear-Discharge decks

2 YEAR | **NO** HOUR LIMIT
LIMITED WARRANTY

OR

5 YEAR | **500** HOUR
LIMITED WARRANTY

* See your local Hustler dealer for complete warranty details

LIMITED
LIFETIME
WARRANTY
FRAME & LEADING EDGE OF DECK

* Original Purchaser Only

www.hustlerturf.com



HUSTLER 
Cutting Grass Not Corners



48" / 54" / 60"

Engines

Kawasaki

FX691
22 hp

Kawasaki

FX730
23.5 hp

Kawasaki

FX850
27 hp

Kohler Command EFI

ECV749
29hp

More Engine Information:

• www.kawpower.com

• www.kohlerengines.com

ENGINE

Starter: 12-volt

Ignition: Electronic

Charging System: 12-volt (see engine manufacturer specs)

Fuel: Unleaded gasoline (see engine manufacturer specs)

Fuel Filter: Replaceable, automotive-type

Air Cleaner: Heavy-duty air cleaner to extend the service interval for excessive, dirty applications and improved performance

Cooling: Air cooled. Fly-wheel fan

Governor: Mechanical

TRACTION DRIVE SYSTEM

Type: Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 20W50 motor oil.

Pumps: Two variable displacement, axial-piston type. Each pump powers one drive-wheel motor. Hydro-Gear PK 12cc Pump

Pump Drive: V-belt drive from engine crankshaft

Hydraulic Lines: Stainless-steel, high-pressure lines with Parker Seal-Lok™ O-Ring Face-Seal fittings.

Final Drive: Direct-drive high-torque wheel motors. One for each drive wheel. Parker TF0240

Filter: Internal

Ground Speed (Infinitely variable)

Forward: 0-11 mph (0-17.7 kph)

Reverse: 0-6 mph (0-9.66 kph)

Steering: SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

Turning: True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes

Service: Hydrostatic dynamic braking

Parking: Automotive-style drum brakes. When steering levers are placed in park position, integral park brakes are automatically engaged.

Tires

Front: 13 x 6.5 – 6, rib tread, pneumatic

Drive: 48 & 54: 24 x 9.5 – 12, 60: 24 x 12.0 – 12

Capacities Fuel System: 10.3 US gal (38.99 l)

GENERAL INFORMATION

Safety Features: Standard foldable ROPS with seat belt. Operator presence system connected to seat, deck clutch and park brake switches. Stabilizer wheels at rear of lawn mower. Side discharge deck with discharge chute and rear discharge deck with deflectors.

Seat: Deluxe vinyl seat with armrests. Fore and aft sliding adjustment.

Construction: Main frame is 1.5 in x 2.0 in x .188 in square steel tubing. Front caster wheels mounted with sealed ball bearings on each wheel. Front caster forks are .50 in (12.7 cm) steel

PTO Clutch: 200 ft. lbs.

Controls: Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators: Engine warning light (low pressure), Fuel gage, Digital hour meter

Cup Holder: Cup holder molded into the left side fuel tank.

ROPS: Certified, 2-post, foldable ROPS with seatbelt.

DIMENSIONS

Height: 53.00 in (133.35 cm) With ROPS folded
71.25 in (172.47 cm) With ROPS up

W/48" Side-Discharge Deck

Length: 80.8 in (205.23 cm)

Overall width: 53.50 in (135.89 cm) w/discharge chute up

Tire-to-tire width: 47 in (119.38 cm)

Weight: 1200 lbs (544 kg)

W/54" Side-Discharge Deck

Length: 80.8 in (205.23 cm)

Overall width: 59.25 in (150.50 cm) w/discharge chute up

Tire-to-tire width: 47 in (129.54 cm)

Weight: 1210 lbs (548 kg)

W/60" Side-Discharge Deck

Length: 83.25 in (211.46 cm)

Overall width: 66 in (168 cm) w/discharge chute up

Tire-to-tire width: 54 in (137.6 cm)

Weight: 1260 lbs (571 kg)

DECKS

Side-Discharge: 48", 54" or 60"

Rear-Discharge: 54", 60"

Type: Free-floating mower deck using three blades with center blade to the front. Includes 3 deck-mounted rollers to improve flotation in rolling and uneven terrain

Deck Lift: Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climbing curbs and trailer more easily.

Construction: Welded steel. Solid 1.5 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial style, box section reinforced front edge. Reinforcements welded onto spindle mount areas. High density, rubberized discharge chute.

Cutting Heights: Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.0 in to 5.5 in (3.81 cm to 13.97 cm)

Mowing Blades: Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

Blade Tip Speed (at 3600 RPM engine speed)

Side-Discharge

Rear-Discharge

48 in: 18,580 fpm

54 in: 18,580 fpm

54 in: 18,340 fpm

60 in: 18,410 fpm

60 in: 18,410 fpm

60 in: 18,410 fpm

Deck Drive: Single V-belt drive from engine with electric clutch to all three spindles. Spring tension idler and large pulleys to extend belt life.

Spindles: Ductile iron casting with steel shafts and sealed ball bearings

Width of Cut

Side-Discharge

Rear-Discharge

48 in: 47.25 in

54 in: 53.10 in

54 in: 53.25 in

60 in: 59.10 in

60 in: 59.25 in

60 in: 59.10 in

Trim Capacity (left side)

48 in: 0.5 in (1.25 cm) w/9.5 in tire = 0.75 in (1.90 cm)

54 in: 2.5 in (6.5 cm) w/9.5 in tire = 4.75 in (12.06 cm)

60 in: 5.9 in (15 cm) w/12 in tire = 5.75 in (14.60 cm)

ACCESSORIES

Flex Forks™: Shock-absorbing front caster forks for a smooth ride and smoother cut

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Catcher: Commercial-duty, 12 bushel, rear-mounted, three-bag catcher

BacVac: Electric accuated DFS catcher system. Easy-on, easy-off versatility. 10 bushel capacity.

No-Flat Caster Tires: (Semi Pneumatic)

Gator™ Blades: Patented mulching blade design

Wavy Blades: Improved performance for mulching

Other Accessories: Light Kit, Steering Lever Extension Kit, Optional Rear Anti-Scalp wheel, Stripe Kit, Hitch Kit, Sand Kit, Suspension Kit for seat.

Specifications subject to change without notice.

