



RAPTOR[°] Legendary Hustler Performance in an entry level zero-turn mower

Ideal For Yards Up To One Acre

HIGHLIGHTS

- 36", 42" or 52" welded-steel deck
- Heavy-duty fabricated frame and deck unmatched durability
- Exclusive SmoothTrak[™] steering responsive, precise control

HUSTLER

RAPTOR

- Patented automatic parking brake
- Smart-Choke™ technology turn the key and go

Checkout the Raptor® 52" Limited! Get all the quality features of a Raptor® 52" model plus a bolstered high-back seat with armrests, low profile 10.5" wide rear tires, 5" wide front tires, engine quard and hour meter.

ENGINE		Front Caster Wheels	Commercial duty steel roller bearings, greasable
Manufacturer	Kawasaki FR691V Kohler 6600 Series HD or	Front Caster Forks	Fabricated 1/4" steel
	7000 Series HD (both with Smart Choke™)	GENERAL	
HP	36" deck: 19HP* - 6600 HD 42" deck: 22HP* - 7000 HD 52" deck: 24HP* - 7000 HD 52" Limited: 23HP* - FR691	Seat	36", 42", 52": Molded vinyl, adjust., suspension springs 52" Limited: Premium seat with armrests
	* Per SAE J1995	Fuel Capacity	3 gallons
Displacement	36" deck: 660cc Kohler 6600 HD 42", 52" deck: 725cc Kohler 7000 HD 52" Limited: 725cc Kawasaki FR	Cup Holder Front Tire	
Cooling	Air cooled	FIOID	52" Limited: 11x5
Engine Warranty	3 year	Drive Tire	36": 18 x 7.00 - 8 42", 52": 18 x 8.50 - 8 52" Limited: 18 x 10.5 - 10
DRIVE SYSTEM			52 Linned. 10 x 10.3 - 10
Туре	Dual hydrostatic	DIMENSIONS	
Transmission	Hydro-Gear EZT	Weight	36": 449 lbs42": 479 lbs52": 503 lbs52" Limited: 503 lbs
Speed	6.5 mph	Height	
Parking Brakes	Patented automatic		52" Limited: 45"
DECKS		Length	
Cutting Width	Side discharge: 36", 42", 52"	Width	36" deck: 37.3" 42" deck: 44.42"
Cutting Heights	1.5"- 4.5"		52" deck: 53.4"
Deck Lift	Hand operated	Tire Width	36" deck: 38.3" 42" deck: 41"
Depth	4.1"		52" deck: 45"
Blades	36", 42" deck: 2 52" deck : 3	PRODUCTIVITY*	
Blade Length	36" deck: 2 - 17.86" x 2.5" x .203" 42" deck: 2 - 20.50" x 2.25" x .188" 52" deck: 3 - 17.86" x 2.25" x .188"	Acres Per Hour	36": 1.89 42": 2.20 52": 2.72
Spindles	Aluminum with 3/4" shafts and triple protection sealed ball bearings	OPTIONAL ACCESSORIES	Grass catcher (non-powered 5.4 bushels) Lights Armrest
Drive	Electric PTO clutch		
Construction	11 ga. fabricated		FlexForks Mulch kit
Spindle Mounts	Reinforced 14 ga.		Engine guard Hour meter
Impact/Trim Areas	1/4" x 3/4" steel bar		Steering extension kit, Stripe kit (52" decks only)
CONSTRUCTION			
Frame	3.25" x 1.5" x .120" steel		* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.
Front Axle	Fabricated with sealed ball bearings		

